

SYSTEMS AND METHODS FOR ADAPTIVE SAMPLING AND ESTIMATING A SYSTEMATIC RELATIONSHIP BETWEEN A PLURALITY OF POINTS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 60/228,347, filed August 28, 2000.

BACKGROUND OF THE INVENTION

[0002] This invention relates generally to systems and methods for estimating a systematic relationship between a plurality of points, and, more particularly, to systems and methods for adaptively sampling points and estimating a form based on coordinate data and normal vector data.

[0003] The estimation of the shape of a form, such as a surface or wave, generally involves the measurement of point data associated with a plurality points on the form. For example, the point data includes a geometrical description of the location of the point on the form. The number and location of the plurality of points are generally determined by a sampling plan, which identifies the location of various sampling points whose measurements may be used to estimate the shape of the entire form. Traditionally, in order to increase the accuracy of the estimation, the number of points measured in the sampling plan are increased. Increasing the number of measured points, however, leads to a number of drawbacks. For example, each point added to the sampling plan adds cost to the estimation process by increasing the time required to measure the point and include the measurement results in the estimation. Thus, traditional sampling plans and form estimators disadvantageously require an increasing amount of time to achieve an increasing level of accuracy.

[0004] Further, for example, the points identified by the sampling plan will dramatically affect the accuracy of the estimation. Many sampling plans include a grid-like array of points having a given spaced-apart relationship. For example, such a grid-like array may be obtained in a "line scan". In order to obtain an accurate

[0005] In addition, typical systems and methods for estimating a form may produce inaccurate results by including erroneous data in the estimation. For example, when measuring a form, a disturbance in the measuring system or foreign matter on the form may result in a measurement that is grossly inaccurate. Such a measurement may be referred to as an “outlier”. If such an outlier is used in estimating the form, then the estimate will not correctly represent the portion of the form adjacent to the outlier. Complex statistical models may be developed to detect and throw out such outliers, but less complex and more efficient solutions are desired.

[0007] Therefore, systems and methods are desired to increase the efficiency, accuracy and completeness of form estimators and their associated sampling plans.

BRIEF SUMMARY OF THE INVENTION

[0008] The systems and methods of the present invention address the drawbacks of the prior art by using the increased information content available when both the normal vector data and position or coordinate data associated with a measured point are utilized to estimate a form or systematic relationship between a plurality of points. Using the information associated with the normal vector and position of the measured points, an indication of how the shape of the form is changing locally is obtained. This information is utilized by an estimation function that predicts the shape of the form or the systematic relationship between the plurality of points. Further, predetermined measurement criteria are utilized to decide if subsequent measurement at predetermined points are required to complete the estimation within desired limits and, if so, the optimal location for the predetermined points.

[0009] In one embodiment, a method for estimating a systematic relationship between a plurality of points, comprises: obtaining coordinate data and normal vector data associated with each point of a starting set of points, where the starting set comprises at least three non-linear points; and determining a first estimated systematic relationship between a plurality of points based on the coordinate data and the normal vector data associated with the starting set of points.

[0010] In another embodiment, a method for estimating a relationship between a plurality of points, comprises: generating a first estimated relationship between the plurality of points based on measured coordinate data and normal vector data, the measured coordinate data comprising a measured value of a vector associated with a point corresponding to a given one of the plurality of points, the normal vector data representative of a local rate of change with respect to the vector associated with the given one of the plurality of points, the first estimated relationship between the plurality of points derived from estimated normal vector data corresponding to at least a portion of the plurality of points; and automatically determining whether further measurements are required based on the estimated normal vector data in combination with predetermined measurement criteria.

[0011] In yet another embodiment, a method of estimating a relationship between a plurality of points, comprises: removing data from a plurality of coordinate data and normal vector data associated with measured points defining a starting set associated with the plurality of points based on estimated normal vector data associated with the measured points, thereby defining a revised starting set; and generating a first estimated relationship between the plurality of points based on the coordinate data and the normal vector data of the revised starting set, the coordinate data comprising a measured value of a vector associated with a point corresponding to a given one of the plurality of points, the normal vector data comprising a the local rate of change associated with the vector of the given one of the plurality of points, the first estimated relationship between the plurality of points derived from estimated normal vector data corresponding to at least a portion of the plurality of points.

[0012] In another embodiment, a method for estimating a systematic relationship between a plurality of points, comprises: receiving measurement data relating to a point associated with the plurality of points; and generating a first estimated systematic relationship between the plurality of points according to a predetermined function representing a multi-dimensional relationship and based on the measurement data, the first estimated systematic relationship having coordinate data and normal vector data.

[0013] In a further embodiment, a computer readable medium for estimating a systematic relationship between a plurality of points, comprises: an estimation module having a predetermined estimation function operative to generate a first estimated systematic relationship between the plurality of points based on coordinate data and normal vector data, the coordinate data comprising a measured value of a vector corresponding to a given one of the plurality of points, the , the first estimated systematic relationship between the plurality of points derived from estimated normal vector data corresponding to at least a portion of the plurality of points; and an adaptive sampling module operative to automatically determine whether further measurements are required based on the estimated normal vector data in combination

[0014] In another embodiment, a system for estimating a systematic relationship between a plurality of points, comprises: an estimator having an estimation function operable for determining a first estimated systematic relationship between the plurality of points, the first estimated systematic relationship between the plurality of points having coordinate data and normal vector data determined from a starting set of measured points associated with the plurality of points; wherein the coordinate data comprise a value of a vector associated with the plurality of points; and wherein the normal vector data comprise a value of a local rate of change of the vector associated with the plurality of points.

5

[0016] And, in yet another embodiment, a system for estimating a systematic relationship between a plurality of points, comprises: an estimator having an estimation function having a predetermined dimensionality and operable for determining a first estimated systematic relationship between the plurality of points, the first estimated systematic relationship between the plurality of points having coordinate data and normal vector data determined from a starting set of measured points associated with the plurality of points; wherein the coordinate data comprise a value of a vector associated with the plurality of points; and wherein the normal vector data comprise a value of a local rate of change of the vector associated with the plurality of points.

[0017] Fig. 1 is a schematic diagram representing one embodiment of a form estimation system of the present invention; and

[0018] Figs. 2 and 3 are flowcharts of one embodiment of a method of estimating the shape of a form.

[0019] In one aspect, systems and methods of the present invention deal with adaptively sampling points of a form to develop an estimate of the form according to an estimation function. The adaptive sampling and form estimation is based on normal vectors associated with the measured points and on predetermined error limits. The form may include, for example, a three-dimensional surface or a waveform.

[0020] In another aspect, systems and methods of the present invention deal with validating the measured data associated with a point, and considering or discarding the measured data based on normal vectors associated with adjacent measured points

and on predetermined error limits.

[0021] Further, the systems and methods of the embodiments of the present invention may be utilized in any system that measures or estimates a systematic relationship between a plurality of points. Such systems include coordinate metrology systems, signal processing systems, reverse engineering systems, computer aided engineering systems, control systems, systems that manage color—such as estimating gradients or removing aliasing, navigation systems, computer vision systems, medical sensing and imaging systems, etc.

[0022] Referring to Fig. 1, in one embodiment, a form estimation system 10 for estimating a shape of a form 12 defined by a plurality of points 14 includes an estimator 16 that receives measured or computed position data 18 and measured or computed normal vector data 20 associated with given points on the form and generates an estimated shape 22 based thereon and according to an estimation function 24. Estimation function 24 processes position data 18 and normal vector data 20, or data error 30 associated therewith, according to a predetermined mathematical model to predict a shape of form 12 based on values associated with the measured or computed points. A measurement device 26 may supply position data 18 and normal vector data 20 to estimator 16. Additionally, estimator 16 may include an adaptive sampling mechanism 28 that determines error 30 associated with the data, determines whether further measurements are required depending on the magnitude of the error, and identifies at least one target point 32 on form 12 for further measurement. Adaptive sampling mechanism 28 is driven by, among other factors, the normal vector data 20, error 30 and a predetermined error limit 34 to automatically make the sampling decision. Further, estimator 16 may include a data verification device 36 for analyzing the measured/computed data or error data with respect to estimated data in order to verify the accuracy of the measured/computed data or error data and remove inaccurate data. Thus, form estimation system 10 utilizes position data and normal vector data to automatically sample points on form 12 according to adaptive sampling mechanism 28 and to

[0023] Form 12 includes a surface, a waveform, any object, or any physical or artificially-generated phenomenon having a measurable shape or having a systematic relationship between points. Plurality of points 14 include points that define the surface of form 12. Each of the plurality of points 14 includes associated data that describe the point, including actual position data 38 and actual normal vector data 40. As used herein, the term “position data” includes any coordinate data that can be represented in vector space, such as, in one example, the position of the point in an x-, y- and z-axis coordinate system. The term “normal vector data” includes data representing the magnitude and direction of a vector positioned normal to a line or plane tangentially positioned with respect to a given point on the form, or data that describes or estimates the instantaneous rate of change of the position data. For example, form 12 may be an object that system 10 measures and compares against a desired nominal shape, or the form may have an unknown shape requiring definition by the system.

8

[0025] Position data 18 and normal vector data 20 respectively may be measured or computed values of position data and normal vector data, as determined by measuring device 26 or other modeling or estimation system, corresponding to actual position data 38 and actual normal vector data 40 at a given point. For example, in a perfect measurement system, the value of position data 18 and normal vector data 20 is substantially equal to the value of actual position data 38 and actual normal vector data 40 at a given point.

[0027] The values of the data associated with estimated shape 22 will vary depending on the predetermined mathematical model utilized by estimation function 24. Estimation function 24 is a computer medium, program, function or processing device that applies a predetermined mathematical model to the received position data 18 and normal vector data 20, or error data 30 associated therewith, in order to generate estimated shape 22. The predetermined mathematical model includes any model that fits the measured data into a shape. Suitable examples of a predetermined mathematical model includes a polynomial model, a cubic spline model, models using Fourier or fractal or wavelet representations, parametric models such as hermite or bezier or b-spline or cubic spline surfaces, parametric solids, swept solids, controlled deformation solids, graph-based solid models, constructive solid geometry or Boolean models, boundary models, space partitioning models such as oct trees, and general

models that preserve adjacency and topology among points in a point set etc.

[0028] Measurement device 26 measures the value of position data and measures or estimates normal vector data at a given point on form 12. Measurement device 26 may include, for example, a coordinate measurement machine (CMM), an oscilloscope, an electronic measurement device, a laser measurement device, an optical measurement device, a mechanical measurement device; devices that measure color, sound, motion, position, temperature, velocity, acceleration and other physical characteristics via mechanical, electrical, electronic, optical, hydraulic sensors; devices that measure simulated signals generated via computer simulation or from data stored in a data base, or any other device capable of measuring and/or estimating the value of position and normal vector data.

[0029] Adaptive sampling mechanism 28 includes a computer medium, program, function or processing device that automatically develops, in a systematic but variable and input-dependent manner, a sampling plan that identifies sampling points on form 12 and determines whether or not further sampling is required. Adaptive sampling mechanism 28 determines position data error 46 and normal vector data error 48, which define estimation error 30, by comparing estimated shape 22 with reference form 50. Reference form 50 includes reference position data 52 and reference normal vector data 54 corresponding to the plurality of points 14 of form 12. Reference form 50 may be a desired shape of form 12. For example, reference form 50 may include data representative of a desired nominal shape, or a desired nominal shape including acceptable error, such as may be required by manufacturing specifications. Alternatively, reference form 50 may be any shape helpful in determining estimated shape 22. For example, reference form 50 may be a flat, planar shape, thereby having point data and normal vector data with values of zero, that can be used as a comparison with the measured data, such as in an instance when the actual or desired shape of form 12 is unknown.

[0030] Adaptive sampling mechanism 28 further includes predetermined error limit 30, which is compared with the estimation error 30 or the measured data to

105076915 "060301
T080905T080901

determine whether or not further measurements are required. Predetermined error limit 30 includes predetermined position data error limit 56 and predetermined normal vector data error limit 58, which may correspond to a desired accuracy for estimated shape 22, such as may be required by quality specifications or such as may be dictated by system constraints. Additionally, adaptive sampling mechanism 28 may include predetermined sample spacing limits 60, which may be received or derived from measurement device 26. Predetermined sample spacing limits 60 may be a value representative of a minimum spacing between points that measurement device 26 is capable of sampling, or which an operator may determine is the minimum spacing based on other system constraints such as desired accuracy or sampling time. Predetermined sample spacing limits 60 may further include a maximum desired spacing between samples, such that measurements that exceed the maximum limit drive the system to take further measurements therebetween. Further, adaptive sampling mechanism 28 may include target point 32, which represents the point corresponding to the maximum absolute value of estimation error 30 or estimated data. In other words, target point 32 is the point at which it most desirable or interesting to take an additional measurement in order to accurately estimate the shape of form 12, as target point is the predicted point deviating the most from reference form 50. Adaptive sampling mechanism 28 may decide not to sample target point 32, however, if the absolute value of the error or estimation at the target point is within predetermined error limits 34, or if the position of the target point is within predetermined spacing limits 60 with respect to previously measured points. It should be noted, however, that predetermined error limit 30 is but one example of a predetermined uncertainty criteria that is utilized to determine the sufficiency of the current estimation. Besides physical and error limitations, as discussed above, the predetermined uncertainty criteria may further includes any other criteria useful for determining whether or not to continue measuring and estimating, such as, for example, rule-based criteria and spatial frequency criteria.

[0031] Additionally, estimator 16 may include data verification device 36 which includes a computer medium, program, function or processing device that analyzes

the validity of measured data 18 and 20 and removes data of questionable validity based on the predicted values associated with estimated shape 22. In other words, data verification device 36 identifies and "throws out" points that are inconsistent with the shape of the form. For example, data verification device 36 may be advantageously utilized when more than a minimum number of measurement data has been gathered to estimate a form, such as in a line scan technique, in order to eliminate inaccurate data from the estimation process. The data of questionable validity, also known as "outlier" data, includes data outside of the limits of the estimated data or estimated data plus error limit for a given point. As an alternative to having outlier data identified as a target point, data verification device 36 removes the outlier data from processing within estimator and thereby removes invalid variability from estimated shape 22. Further, data verification device 36 may be utilized to generate a less complex estimate of the shape or the simplest estimate. Such less complex estimates may be useful in reverse engineering applications and computer aided design applications, where simpler forms are desirable as they are more conducive to further computer processing or to fit reduced order models that are conducive to computer-aided engineering methods.

[0032] Referring to Fig. 2, one embodiment of a method for estimating the shape of a form having a plurality of points includes identifying a starting set of points on the form for measurement (Block 70). The starting set of points are evaluated to determine whether or not they meet the predetermined sample spacing limits (Block 72). If the starting set does not meet the limits, such as if the points are too closely spaced or spaced too far apart, then a new starting set of points is generated that meet the spacing limits (Block 74). If the starting set does meet the limits, then the next action may be taken (see Block 76, described below). In one embodiment, the starting set of points define a boundary of the form, and the starting set comprises at least three non-linear points. As such, the form is covered by a "triangular patch" defined by the three points. In one embodiment, one or more triangular patches are identified to cover the portion of the form of interest, where adjacent triangular patches may share all or a portion of a side of a triangular patch. Once one triangular patch is

evaluated using the described methodology, the system moves on to the remaining triangular patches until the entire portion of interest of the form has been evaluated. It should be noted that any number of points may be utilized, from a single point to a plurality of points, with the number of points varying depending on the estimation function utilized. Further, it should be noted that rectangular, square, or any other shaped patches may also be utilized. The method works the same for any type of patch -- the boundaries could be curves, discrete point sets, or any rule sets that describe which points are on the surface and which are not. Further, surface models that have boundaries outside of the zone formed by the sample points may also be used. Alternatively, the starting set of points may comprise a single line, or two or more lines of spaced-apart points, for example a grid-like array of spaced-apart points, such as may typically be utilized in a line scan type of sampling plan. In one embodiment utilizing such a spaced-apart starting set, the triangular patches are chosen from among the plurality of spaced-apart points such that the three points are not co-linear. In such a manner, a portion of a surface perpendicular to an initial line scan may be evaluated.

[0033] Measurements of the values of the position data and the measured or computed normal vector data are then determined for each point of the starting set of points (Block 76). For example, the measuring device 26 (Fig. 1) may translate to each point of the starting set and obtain the desired data. It should be noted, however, that the identification of the starting set and the measurement of the position and normal vector data associated therewith are optional actions, and that the measured position and normal vector data for a given starting set may simply be supplied to the system.

[0034] Upon receiving the measured position and measured or computed normal vector data, the method involves determining error data associated with the measured position and measured or computed normal vector data (Block 78). In one embodiment, the error data comprises position data error and normal vector data error determined as the difference between the measured position and normal vector data

[0035] Using the error data and an estimation function, the method predicts the shape of the form (Block 80). As described above, the estimation function includes a predetermined mathematical model for deriving estimated values associated with the form based on the data values of the measured points. The measured values associated with the predicted shape are analyzed by data verification device, and invalid data is removed from the prediction (Block 82). This action is applicable, for example, when more than a minimum number of measurement samples have previously been obtained, such as in a line scan. As such, the shape of the form is revised and an estimated shape of the form is generated (Block 84).

[0036] The method then automatically analyzes the data associated with the estimated shape to determine a target point to measure next (Block 86). The target point is the point most likely to contain information relevant to determining the best prediction of the actual shape of the form. In one embodiment, the target point is identified by analyzing the error data associated with the measured and predicted values of the estimated shape, and determining the point having a maximum absolute error value. Then, the estimated error data associated with the target point is compared with the predetermined error limits (Block 88). If the estimated error data associated with the target point is less than or equal to the predetermined error limit, then the estimated shape of the form is output (Block 90). If the estimated error data associated with the target point is greater than the predetermined error limit, then the target point position is evaluated with respect to the predetermined minimum sample spacing limit (Block 92). If the target point position violates the predetermined minimum sample spacing constraint, then no further measurements may be taken and

[0039] Example embodiments of the present invention have now been described. It will be appreciated that these examples are merely illustrative of the invention. Many variations and modifications of the invention will be apparent to those skilled in the art. For example, system 10 may only include estimator 16, where the estimator may remotely receive and process the measured data to determine estimated shape 22. Thus, the present invention is defined by the following claims and their equivalents.